

# WT18-3P421

W18-3

**SMALL PHOTOELECTRIC SENSORS**

**SICK**  
Sensor Intelligence.



Illustration may differ



### Ordering information

| Type       | Part no. |
|------------|----------|
| WT18-3P421 | 1026383  |

Other models and accessories → [www.sick.com/W18-3](http://www.sick.com/W18-3)

### Detailed technical data

#### Features

|                                        |                                                        |
|----------------------------------------|--------------------------------------------------------|
| <b>Sensor/ detection principle</b>     | Photoelectric proximity sensor, Background suppression |
| <b>Dimensions (W x H x D)</b>          | 17.6 mm x 75.5 mm x 33.5 mm                            |
| <b>Housing design (light emission)</b> | Rectangular                                            |
| <b>Sensing range max.</b>              | 10 mm ... 1,000 mm <sup>1)</sup>                       |
| <b>Sensing range</b>                   | 50 mm ... 1,000 mm <sup>1)</sup>                       |
| <b>Type of light</b>                   | Infrared light                                         |
| <b>Light source</b>                    | LED <sup>2)</sup>                                      |
| <b>Light spot size (distance)</b>      | Ø 30 mm (600 mm)                                       |
| <b>Wave length</b>                     | 870 nm                                                 |
| <b>Adjustment</b>                      | Double teach-in button                                 |

<sup>1)</sup> Object with 90 % reflectance (referred to standard white, DIN 5033).

<sup>2)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

#### Mechanics/electronics

|                       |                                   |
|-----------------------|-----------------------------------|
| <b>Supply voltage</b> | 10 V DC ... 30 V DC <sup>1)</sup> |
|-----------------------|-----------------------------------|

<sup>1)</sup> Limit values when operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not exceed or fall below U<sub>V</sub> tolerances.

<sup>3)</sup> Without load.

<sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

<sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>7)</sup> C = interference suppression.

<sup>8)</sup> D = outputs overcurrent and short-circuit protected.

|                                        |                                                       |
|----------------------------------------|-------------------------------------------------------|
| <b>Ripple</b>                          | < 5 V <sub>pp</sub> <sup>2)</sup>                     |
| <b>Power consumption</b>               | 55 mA <sup>3)</sup>                                   |
| <b>Switching output</b>                | PNP                                                   |
| <b>Output function</b>                 | Complementary                                         |
| <b>Switching mode</b>                  | Light/dark switching                                  |
| <b>Output current I<sub>max.</sub></b> | 100 mA                                                |
| <b>Response time</b>                   | < 700 µs <sup>4)</sup>                                |
| <b>Switching frequency</b>             | 700 Hz <sup>5)</sup>                                  |
| <b>Connection type</b>                 | Male connector M12, 4-pin                             |
| <b>Circuit protection</b>              | A <sup>6)</sup><br>C <sup>7)</sup><br>D <sup>8)</sup> |
| <b>Weight</b>                          | 40 g                                                  |
| <b>Housing material</b>                | Plastic, ABS                                          |
| <b>Optics material</b>                 | Plastic, PMMA                                         |
| <b>Enclosure rating</b>                | IP67                                                  |
| <b>Ambient operating temperature</b>   | -40 °C ... +60 °C                                     |
| <b>Ambient storage temperature</b>     | -40 °C ... +75 °C                                     |
| <b>UL File No.</b>                     | NRKH.E181493 & NRKH7.E181493                          |

1) Limit values when operated in short-circuit protected network: max. 8 A.

2) May not exceed or fall below U<sub>v</sub> tolerances.

3) Without load.

4) Signal transit time with resistive load.

5) With light/dark ratio 1:1.

6) A = V<sub>S</sub> connections reverse-polarity protected.

7) C = interference suppression.

8) D = outputs overcurrent and short-circuit protected.

## Safety-related parameters


|                         |           |
|-------------------------|-----------|
| <b>MTTF<sub>D</sub></b> | 662 years |
| <b>DC<sub>avg</sub></b> | 0%        |

## Classifications

|                       |          |
|-----------------------|----------|
| <b>ECI@ss 5.0</b>     | 27270904 |
| <b>ECI@ss 5.1.4</b>   | 27270904 |
| <b>ECI@ss 6.0</b>     | 27270904 |
| <b>ECI@ss 6.2</b>     | 27270904 |
| <b>ECI@ss 7.0</b>     | 27270904 |
| <b>ECI@ss 8.0</b>     | 27270904 |
| <b>ECI@ss 8.1</b>     | 27270904 |
| <b>ECI@ss 9.0</b>     | 27270904 |
| <b>ETIM 5.0</b>       | EC002719 |
| <b>ETIM 6.0</b>       | EC002719 |
| <b>UNSPSC 16.0901</b> | 39121528 |


Connection diagram

Cd-083



Characteristic curve


WT18-3 (Ex), infraret, 1,000 mm



- ① Sensing range on black, 6% remission
- ② Sensing range on gray, 18 % remission
- ③ Sensing range on white, 90% remission

Sensing range diagram


WT18-3 (Ex), infraret, 1,000 mm



- Sensing range
- ① Sensing range on black, 6% remission
  - ② Sensing range on gray, 18 % remission
  - ③ Sensing range on white, 90% remission

## Adjustments possible


Double teach-in button



① Sensing range adjustment: double teach-in button

## Dimensional drawing (Dimensions in mm (inch))

WTB18-3, double teach-in button



- ① Standard direction of the material being detected
- ② Center of optical axis, sender
- ③ Center of optical axis, receiver
- ④ Mounting hole  $\varnothing$  4.1 mm
- ⑤ LED indicator yellow: Status of received light beam
- ⑥ LED indicator green: Supply voltage active
- ⑦ Sensing range adjustment: double teach-in button
- ⑧ M12 male connector, 4-pin or 2 m cable

## Recommended accessories

Other models and accessories → [www.sick.com/W18-3](http://www.sick.com/W18-3)

|                                                                                     | Brief description                                                                | Type       | Part no. |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|------------|----------|
| Mounting brackets and plates                                                        |                                                                                  |            |          |
|  | Mounting bracket with hinged arm, steel, zinc coated, mounting hardware included | BEF-WN-W18 | 2009317  |

|                                                                                   | Brief description                                                                                                                     | Type               | Part no. |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| Plug connectors and cables                                                        |                                                                                                                                       |                    |          |
|  | Head A: female connector, M12, 4-pin, straight, A-coded<br>Head B: Flying leads<br>Cable: Sensor/actuator cable, PVC, unshielded, 5 m | YF2A14-050VB3XLEAX | 2096235  |
|  | Head A: male connector, M12, 4-pin, straight<br>Head B: -<br>Cable: unshielded                                                        | STE-1204-G         | 6009932  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)